



SOVEREIGN

TECHNICAL INFORMATION SHEET

PASSYFIER VENT MARK 2

The Passyfier Vent Mark 2 contains a permeable membrane within the main plastic circular tube. This encourages moisture migration due to the differences between external and internal temperature and air pressure. The membrane acts as a molecular sieve, allowing water vapour to pass to the outside whilst resisting rapid air movement and therefore heat loss. The Passyfier Vent is also fitted with a specially designed cowl which counteracts the detrimental effects of external wind on performance.

The 'Passyfier' vent provides an opening on a section of wall normal to the airflow direction with an effective area well in excess of the minimum requirement.

Airflow through the opening is controlled automatically by the intervening mineral wool slab and thereby avoids undue draughts.

It is important to realise that the release of moisture vapour pressure within a dwelling to avoid condensation does not require a specific ventilation rate.

KEY FEATURES

- Is a passive dehumidifier
- Transparent to water vapour
- No moving parts
- Works passively 24 hours a day
- Makes no noise
- Low installation cost
- Special cowl design

The moisture vapour pressure within a dwelling is always higher than the outside pressure therefore there will always be an escape of moisture vapour by the diffusion process through the Passyfier vent.

The diffusion process is slow compared with mechanical ventilation and would not cope with the copious amount of water vapour produced in a short time scale without the combined use of mechanical ventilation in kitchens and bathrooms.

Its main use is in habitable rooms where it operates continuously without noise and over a 24 hour period can extract up to 1litre of water/day even at low vapour pressures.

Dimensions

Main tube diameter	102 mm
Main tube length	350 mm

BENEFITS

- Affordable, one off cost
- Reduces draughty air flow and heat loss
- No running costs
- Works at peak condensation times
- No night time disturbance from compressors or fans
- 20% more effective than a conventional cowl/grill

Condensation

Tenants and property owners usually notice condensation when it presents itself on decorations often causing discoloration and black mould growths.

Air within the living environments becomes saturated with water vapour. The main causes of air saturation are: boiling kettles, cooking, drying clothes, the use of non-flued heating and even breathing. When these conditions prevail, the air inside the property becomes saturated. The amount of water vapour contained in air is related to the air temperature, hence the term 'Relative Humidity'. Warm air can contain large amounts of water vapour. When saturated air begins to cool, it no longer has the ability to hold the water as vapour and at this point will release it onto cold surface in the form of condensation. In traditionally constructed properties with open fires, ventilated suspended timber floors and sash windows, condensation (in most cases) required no extra consideration. However many old properties have been renovated. In some cases solid floors have been laid, double-glazing has been installed and the houses have been generally draught proofed to conserve expensive heat. Many new properties have been constructed with little or no thought to Humidity Control and thus the need for Humidity controlling devices.

The Humidity Controlling Options

Once it has been established that condensation is occurring, the question arises of how to control it. Options take many turns:

- (1) Install air bricks and heat the property; (this can be physically effective but not cost effective as most of the heat created inside the property ends up heating the street outside.

- (2) Install a portable dehumidifier; this again can be physically effective but there are running costs, noise and the occupant need to empty the water container regularly.

- (3) Install humidistat controlled fans which have installation and running costs.

- (4) Install positive pressure systems with installation costs, running costs and a noise consideration.

The Passyfier Vent

The Passyfier (passive dehumidification system) was invented and developed in the UK as one answer to the problem of condensation.

Condensation control is an ever-increasing market with many solutions most of which can be effective. However, the effectiveness of other products often causes expense to the property owner with running costs, noise and maintenance programmes often required for these systems to remain effective.

How does the Passyfier Vent Work?

The Passyfier contains no moving parts and works on basic principles accepted in building physics. When a combination of internal room temperatures and humidity is higher than it is externally, the vapour pressure difference causes the moist air to ventilate outwards through the Passyfier's porous membrane into the cooler external air.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice, please ensure you have the latest updated information.

SOVEREIGN

Sovereign Chemicals Limited,
Park Road, Barrow in Furness,
Cumbria.
Tel: 01229 870800
Fax: 01229 870850
Technical Support Line: 0845 603 0722
Web: www.sovchem.co.uk
Email: sales@sovchem.co.uk